

TECHNICAL SPECIFICATION (As per IS Specification) (OPzS-HDP)

Model name as per IS Specification	UBPL Model	C ₁₀ Cap. Discharge to 1.85V	Cell Dimension mm. (H1-Height up to lid top) (H2-Overall max. Height)			Weight (Kg)		Electrolyte Volume Approximately Liters
			L	W	H1/H2	Dry	Filled	
IS 1651:2013	Model	Ah						
T65S HDP	2DS40	65	103	206	345/450	8.6	13.6	4.05
T80S HDP	2DS50	80	103	206	345/450	8.6	13.6	4.05
T100S HDP	3DS40	100	103	206	345/450	10.7	15.1	3.60
T150S HDP	4DS40	150	103	206	345/450	12.5	16.5	3.40
T175S HDP	5DS40	175	124	206	345/450	15.0	19.8	4.10
T200S HDP	4DS63	200	124	206	460/580	18.4	25.3	6.40
T250S HDP	5DS63	250	145	206	460/580	20.8	30.1	7.70
T300S HDP	6DS63	300	166	206	460/580	24.2	35.2	9.60
T350S HDP	7DS63	350	166	206	460/580	28.1	36.6	7.80
T450S HDP	6DS80	450	191	210	636/730	31.1	43.0	11.0
T500S HDP	7DS80	500	191	210	636/730	41.0	57.5	13.8
T550S HDP	8DS80	550	191	210	636/730	43.5	59.5	13.0
T650S HDP	9DS80	650	191	210	636/730	47.1	62.5	12.0
T750S HDP	10DS80	750	203	210	636/730	53.0	87.0	17.8
T850S HDP	12DS100	850	275	210	636/730	71.5	95.5	20.5
T1000S HDP	11DS100	1000	275	210	762/880	80.0	108.0	23.5
T1100S HDP	12DS100	1200	275	210	762/880	82.0	110.0	25.8
T1400S HDP	15DS100	1400	397	212	762/880	108.0	152.0	36.5
T1800S HDP	20DS100	1800	487	212	762/880	130.0	185.0	45.5
T2000S HDP	22DS100	2000	487	212	762/880	142.0	193.2	43.0
T2200S HDP	24DS100	2200	576	212	762/880	163.0	228.0	54.5
T2400S HDP	26DS100	2300	576	212	762/880	168.0	240.0	53.5
T2500S HDP	28DS100	2500	576	212	762/880	181.0	243.0	52.0